



Specification

INNOVA М О Д У Л Ь

| | |
|-------------------|---------------------------------|
| Description | Machine Tufted Carpet |
| Construction | Tufted Textured Loop Tipsheared |
| Yarn Component | 100% Nylon 6 |
| Dye Method | Solution Dyed |
| Pile height | 6.5+/-0.3mm |
| Total height | 8.5+/-0.3mm |
| Pile weight | 1000+/-5% g/m ² |
| Total weight | 2300+/-5% g/m ² |
| Primary Backing | P.P.woven cloth |
| Secondary Backing | Soft Action Back |
| Width | 3.66m |

Testing

| | |
|---|---------------------------------|
| Electrostatic propensity | AATCC 134-2011 \leq 3. 5KV |
| Smoke density | ASTM E 662-15a Less than 450DMC |
| Flooring radiant panel test | ASTM E 648-03 (NFPA 253) |
| Flammability | BS EN13501-1 Class Cfl-s1 |
| Stain Resistance | AATCC175 Rating10 |
| ColorFastness to light | AATCC 16.3 Rating 5 |
| ColorFastness to crocking | AATCC 165 Rating 5 |
| ColorFastness to water | AATCC 107 Rating 5 |
| Antimicrobial | AATCC 174 part II |
| Indoor Air Quality-CRI Green Label Plus | GLP1350 |

Performance

| | |
|---------------------|-----------------------|
| Wear Classification | Heavy commercial (33) |
| Wear Warranty | 10 Years |