

Interface®

High Rise

Product definition	Tufted Patterned Textured Loop Tile						
Pile Material	100% BCF Solution Dyed Nylon contains pre-consumer recycled content						
Pile Yarn Weight	650g/m ² ± 5%						
Total Weight	4534g/m ² ± 5%						
Pile Height	4.0 ± 0.3 mm						
Total Thickness	7.6 ± 0.5 mm						
Gauge/Ends per 10cm	1/12 - 47.2						
Tufts per m2	169,920 ± 5%						
Backing Type	Graphlex®						
Wear Classification	EN 1307 33 Heavy Contract						
Radiant panel	(EN ISO 9239/1) Euroclass CfI S1 (EN ISO 13501)						
Dimensional Stability	≤ 0.2% (ISO 2551 / EN 986)						
Impact Sound Insulation (ΔLw)	26dB						
Rating of Sound Absorption	α _w (EN ISO 11654)						
Sound Absorption	125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	(EN ISO 354) α _s
Style number	3214000405			4m ² - 16 Tiles per Box (50 cm x 50 cm ± 0.15%)			

CE

DOP:
textile floor covering
EN 1307

www.pro-din.info

ISO 9001
ISO 14001

BRICK

QUARTER - TURN

ASHLAR

MONOLITHIC

33

26dB

6 (ISO)

≥ 2.4 (EN)

Interface Europe Ltd reserve the right to change or modify specifications

www.interface.com



Mission Zero:
our promise to eliminate any
negative impact our company
may have on the environment
by the year 2020.