

Interface®

Concrete Mix - Broomed

Product definition	Tufted Patterned Level Loop Tile						
Pile Material	100% Recycled Solution Dyed Nylon						
Pile Yarn Weight	706g/m ² ± 5%						
Total Weight	4634g/m ² ± 5%						
Pile Height	2.6 ± 0.5 mm						
Total Thickness	6.7 ± 0.5 mm						
Gauge/Ends per 10cm	5/64 - 50.4						
Tufts per m2	194,040 ± 5%						
Backing Type	Graphlex®						
Wear Classification	EN 1307 33 Heavy Contract						
Radiant panel	(EN ISO 9239/1) Euroclass CfI S1 (EN ISO 13501)						
Dimensional Stability	≤ 0.2% (ISO 2551 / EN 986)						
Impact Sound Insulation (ΔLw)	25dB (EN ISO 10140-3)						
Rating of Sound Absorption	α _w 0.20 (EN ISO 11654)						
Sound Absorption	125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	(EN ISO 354)
	0.02	0.03	0.10	0.21	0.36	0.42	α _s
Style number	33814	4m ² - 16 Tiles per Box (50 cm x 50 cm ± 0.20%)					

EN 14041



DOP: 1037/119255
textile floor covering
EN 1307



A05DCE50
www.pro-din.info



install with TacTiles®



Interface Europe Ltd reserve the right to change or modify specifications

www.interface.com



Mission Zero:
our promise to eliminate any negative impact our company may have on the environment by the year 2020.