

QUALITY  
ORDER CODE

DATE: **26/03/2018**  
REPLACES: 13/02/2018

WIDTH (±) cm  
TYPE  
GAUGE AND TYPE  
TEXTURING  
DYEING/PRINT METHOD

PILE COMPOSITION  
FIBRE BRAND  
WOOLMARK  
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m<sup>2</sup>  
TOTAL WEIGHT (± 15%) gr/m<sup>2</sup>

EFFECTIVE PILE HEIGHT (±) mm  
TOTAL HEIGHT (±) mm  
NUMBER OF KNOTS (±) m<sup>2</sup>  
STITCHES OVER WIDTH (±) / 10 cm  
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm  
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m  
PILE IN/OUT

**LANO CLASSIFICATION**

BEDROOM  
LIVING ROOM  
OFFICE  
CASTOR ROLLCHAIRS DOMESTIC USE  
CASTOR ROLLCHAIRS PROFESSIONAL USE  
STAIRS DOMESTIC USE  
STAIRS PROFESSIONAL USE  
ELECTROSTATIC BEHAVIOUR  
UNDERFLOOR HEATING  
BATH ROOM  
NON-FRAY  
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER  
DIBT

UPEC n°  
CLASSIFICATION

HQE  
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION  
CLASSIFICATION BS7131

**HARMONY SMB**  
**HRM**

± 400 & 500  
COLLECTION  
1/10" CUT PILE

PIECE DYED

PA

WOVEN

SMART BACK

± 1.265  
± 2.260

± 7,5  
± 9,5  
± 165.480  
± 39,40  
± 42,00

±  
±

±

✓  
✓  
✓  
✓  
✓  
✓

C67F61C0

Cl. 32  
Commercial General



LC4



Bfl-s1



QUALITY

DIMENSIONAL STABILITY

EN 986

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 25



SOUND ABSORPTION

(±)

α<sub>s</sub>

ISO 354 - 125 Hz

±

(±)

250Hz

±

(±)

500Hz

±

(±)

1000Hz

±

(±)

2000Hz

±

(±)

4000Hz

±

SOUND ABSORPTION

(±)

α<sub>w</sub>

EN ISO 11654

±

THERMAL RETENTION

(±) m<sup>2</sup>/KW

ISO 8302

±

TOG rating

(±)

± 1,5

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤

SURFACE RESISTANCE RoT

(±) ohm

ISO 10965

≤

SURFACE RESISTANCE RdT

(±) ohm

ISO 10965

≤

LIGHTFASTNESS

ISO 105-B02

≥ 5

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 3-4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 3

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01


≥ 3-4

WATERFASTNESS STAINING

ISO 105-E01

≥ 2-3

LABEL CE



RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN  
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

COLOURS

AVAILABLE FROM

AVAILABLE FROM



<u>SMB 400</u>	<b>HRM</b>	<u>SMB 500</u>
090	AUBERGINE	090
110	CARMINE	110
120	CORAL	120
150	SAHARA	150
210	TOBACCO	210
250	MAGNOLIA	250
440	IVORY	440
450	SAND	450
720	BLUE CAPE	720
780	STEEL	780
790	MIDNIGHT	790
810	CHARCOAL	810
830	ASH	830
860	GRANITE	860
870	SILVER	870
880	PEARL	880

<u>SMB 400</u>	<b>HRM</b>	<u>SMB 500</u>

WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE