Current



Installation Method



Interface European Manufacturing BV reserve the right to change or modify specifications.

Product Current Colour 4192008 Lobelia

Product Specifications						
Product Number	4192					
Product Construction	Tufted Pat	Tufted Patterned Structured Loop Pile				
Yarn System	100% Sol	100% Solution Dyed Nylon				
Standard Backing	Graphlex®	Graphlex®				
Optional Backing(s)	ReCushio	ReCushion Bac [®] ,SONE [®]				
Size – Packaging	50 x 50 cr	50 x 50 cm – 4 m² Box				
Pile Yarn Weight	531 g/m² ± 5%					
Total Weight	4119 g/m² ± 5%					
Pile Height	2.7 mm +15% / - 10%					
Total Thickness	6.1 mm ± 0.5 mm					
Gauge – Ends per 10 cm	1/12 - 47.2					
Tufts per m ²	207,680/m² ±5%					
Performance Specifications						
Wear Classification	EN 1307 33 Heavy Contract					
Castor Chair Rating	≥2.4 (EN 985) Continuous Use					
Flammability	(EN ISO 9239-1) Euroclass Cfl-s1 (EN 13501-1)					
Light Fastness	≥7 (ISO 1	05-B02)				
Light Reflectance Value (LRV)	LRV – L value LRV – Y value					
	36.4	36.4 9.2				
Dimensional Stability	≤0.2% (ISO 2551/EN 986)					
Impact Sound Insulation ΔL_w EN ISO 10140-3	25 dB					
Rating of Sound Absorption (α_w) EN ISO 11654	0.20					
Sound Absorption (α_s)	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
EN ISO 354	0.01	0.05	0.08	0.22	0.34	0.44

Environmental Specifications

Linvironmental Sp	Jecifications						
Total Recycled Cont	tent	47.8%	47.8%				
Pre-Consumer (1	umer (Total) 47.8%						
Post-Consumer (Total)			0%				
Yarn Recycled Content			0%				
Pre-Consumer (Yarn)			0%				
Post-Consumer (Yarn)			0%				
Indoor Air Quality			GUT Prodis ID 49BAADDD				
		<u>GLP 98</u>	<u>19</u>				
		French	Α+				
		Danish I	Indoor Climate				
		<u>GUI Sta</u>	ndard				
Potential Green Buil	ding Contribution						
BREEAM (UK/In	ternational)	View por	tential BREEAM contrib	oution			
BRE Green Guid	e Ratings						
Commercial	Domestic	Education	Health	Retail (Fashion)	Retail (Durability)		
Not Available	Not Available	Not Available	Not Available	Not Available	Not Available		
LEED (US/Intern	ational)	View Po	tential Leed Contribution	on			
HQE (France)		View Po	tential HQE Contributio	n			
DGNB (Germany	()	View Po	tential DGNB Contribut	tion			
Environmental Pr	roduct Declaration	wc_eu-e	pd-int-20180115-curre	nt-cbc1-en			

Interface[®]

Carbon Footprint			
Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method		
Raw Materials and Production	8.05 kg CO ₂ eq./m ²		
Delivery and Installation	0.64 kg CO ₂ eq./m ²		
Use (10 Years)	3.24 kg CO ₂ eq./m ²		
End of Life (Waste to Energy)	5.69 kg CO ₂ eq./m ²		
Total (10 Years Lifetime)	17.62 kg CO ₂ eq./m ²		
Carbon Neutral Floors™	Standard		
Installation Impacts			
Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below:		
	Non-directional – 1-2%		
	For reference: 2 m wide broadloom typically generates 7-10% installation waste		
TacTiles®	Optimised for glue-free installation with TacTiles [®] connectors with virtually zero VOCs		
End of Life Options			
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.		
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.		
Waste to Energy	Can be incinerated in appropriate waste to energy plant.		
Technical Information			
Installation	See recommended Interface installation guidelines		
Maintenance	See recommended Interface maintenance guidelines		
Warranty	15 years		
Manufacturing Location	ISO 9001 & 14001 Certified Facilities in Europe		

Performance Qualifications



Certifications

