WW865 Interface®



Installation Method





Herringbone

Ashlar

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see

www.interface.com/disclaimer.

Product Specifications		
Product Number	28210AK00	
Product Construction	Tufted Pattern Loop	
Yarn System	100% Recycled Content Type 6 Nylon	
Yarn Manufacturer	Aquafil	
Dye Method	100% Solution Dyed	
Soil/Stain Protection	Protekt ^{2®}	
Preservative Protection	Intersept®	
	Imperial	Metric
Tufted Yarn Weight	17 oz/yd²	576 g/m²
Machine Gauge	1/10 in	39.4 ends/10cm
Pile Height	0.11 in	2.8 mm
Pile Thickness	0.057 in	1.4 mm
Stitches	10 /in	39.4 ends/10cm
Pile Density	10,737 oz/yd³	398,125.6 g/m³
Size	9.845 in x 39.38 in	25cm x 1m
Performance Specifications		
Radiant Panel	(ASTM E-648) Passes	
Smoke Density	(ASTM E 662) ≤ 450	
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)	
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's	
Static	(AATCC - 134) < 3.0 KV	
Dimensional Stability	AACHEN Din 54318 <.10%	
Traffic Classification	Severe	
Fiber Modification Ratio	1.9 to 2.2	
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition	
Environmental Specifications		
Total Recycled Content	76%	
Recycled Content (Post Industrial)	68%	
Recycled Content (Post Consumer)	8%	
Indoor Air Quality	Green Label Plus #GLP0820	
Ingredients and Life Cycle Impacts	Environmental Product Declaration	
Other Environmental Claims	3rd Party Verified Carbon Neutral NSF/ANSI-2440 Gold - Sustainability Assessment	
End Of Life	Carpet to Carpet Recycling	
Technical Information		
Installation	See Interface Installation Guidelines online	
Maintenance	Recommended Interface Maintenance Guidelines	
Reclamation	Recyclable through ReEntry $^{\!0}$ - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)	
Warranty	15 Year Standard Carpet Warranty	
Standard Backing	GlasBac [®]	
Backing Options	GlasBac [®] , GlasBac [®] RE, CushionBac Renew™	
Tile Size Options	25cm x 1m	
Manufacturing Location	ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States	

Page 1 of 1 February 26, 2019