

QUALITY
ORDER CODE

DATE: **4/12/2018**
REPLACES: 13/09/2017

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

MACCAN SB
MAA

± 400
COLLECTION
1/10" LOOP PILE

PIECE DYED

PA 6 / PA 6.6

NON WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 705
± 2.150

± 3,4
± 6,5
± 90.620
± 39,40
± 23,00

±
±

±

✓
✓
✓
✓
✓
✓
✓
ANTISTATIC
✓

312CF98F

18/317
U3P3E1C0

Cl. 33
Commercial Heavy



LC2



Bfl-s1




LOW RADIUS

QUALITY


IMPACT SOUND INSULATION	(±) dB	ISO 140/8
THERMAL RETENTION	(±) m ² /KW	ISO 8302
TOG rating	(±)	
PERMANENTLY ANTISTATIC	(±) volt	ISO 6356
LIGHTFASTNESS		ISO 105-B02
RUBBINGFASTNESS DRY		ISO 105 X12
RUBBINGFASTNESS WET		ISO 105 X12
WATERFASTNESS CHANGE IN COLOUR		ISO 105-E01
WATERFASTNESS STAINING		ISO 105-E01

MACCAN SB


± 20 

± 0,07

± 0,7

≤ 2000 

≥ 5
 ≥ 3-4
 ≥ 3
 ≥ 3-4
 ≥ 2-3



ALL-OVER STICK DOWN
 WITH EC1 APPROVED ADHESIVE

LABEL CE

RECOMMENDED INSTALLATION

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

MANUFACTURING TOLERANCE

AVAILABLE FROM

AVAILABLE FROM

COLOURS



SB 400	MAA
120	CORAL
180	RUM
220	ACORN
250	MAGNOLIA
380	BRONZE
400	COFFEE
590	MOSS
700	NAVY
710	ATLANTIC
720	BLUE CAPE
810	CHARCOAL
830	ASH
840	MOONSHINE
860	GRANITE

SB 400	MAA
---------------	------------

WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE