




















Technical specifications

Showtime meets the requirements of EN1307

		Showtime Colour	Showtime Graphic	
	Total thickness	ISO 1765	4.9 mm	4.9 mm
	Wear layer thickness	ISO 1766	1.6 mm	1.6 mm
	Total weight	ISO 8543	1150 g/m ²	1150 g/m ²
	Collection size		17	20
	Commercial use	EN ISO 10874	Class 32	Class 32
	Pile composition		100% polyamide	100% polyamide
	Pile weight	ISO 8543	280 g/m ²	280 g/m ²
	Backing		100% recycled polyester	100% recycled polyester
	Roll width		200 cm	200 cm
	Roll length		± 40 m	± 40 m
	Impact noise reduction	EN ISO 717-2	20 dB	20 dB
	Sound absorption	EN ISO 354	$\alpha_w = 0,15$ (H)	$\alpha_w = 0,15$ (H)
	Castor chair continuous use	ISO 4918	$r \geq 2,4$	$r \geq 2,4$
	Colour fastness to light	ISO 105/B02	≥ 6	≥ 6
	Colour fastness to water	ISO 105/E01	$\geq 3-4$	$\geq 3-4$
	Colour fastness to rubbing wet	ISO 105-X12	≥ 3	≥ 3
	Colour fastness to Rubbing dry	ISO 105-X12	$\geq 3-4$	$\geq 3-4$
	Indoor air emissions: TVOC after 28 days	EN 16516	$\leq 0,1$ mg/m ³	$\leq 0,1$ mg/m ³
	Recycled content		Needlefelt sheet are manufactured with at least 50% recycled content by weight	
	Installation method		↑↑	↑↓

Showtime meets the requirements of EN 14041

			0300721-DoP-010	0300721-DoP-010
	Product code	EN 14041:2004	0300721-DoP-010	0300721-DoP-010
	Reaction to fire	EN 13501-1	C _{fl} -s1, G, NCS	C _{fl} -s1, G, NCS
	Slip resistance	EN 13893	$\mu > 0.30$	$\mu > 0.30$
	Thermal conductivity	EN 12524	0.06 W/mK	0.06 W/mK
	Body voltage	ISO 6356	< 2.0 kV	< 2.0 kV



All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
 All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.
 The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.