


# Interface®




## Lima

<b>Product definition</b>	Tufted Patterned Textured Loop Tile					
<b>Pile Material</b>	100% Solution Dyed Nylon contains recycled content					
<b>Pile Yarn Weight</b>	650g/m <sup>2</sup> ± 5%					
<b>Total Weight</b>	4466g/m <sup>2</sup> ± 5%					
<b>Pile Height</b>	4.3 mm ± 0.5 mm					
<b>Total Thickness</b>	7.1 mm ± 0.5 mm					
<b>Gauge/Ends per 10cm</b>	1/12 - 47.2					
<b>Tufts per m2</b>	174,640 ± 5%					
<b>Backing Type</b>	Graphlex®					
<b>Wear Classification</b>	EN 1307 33 Heavy Contract					
<b>Radiant panel</b>	(EN ISO 9239/1) Bfl S1 (EN ISO 13501)					
<b>Dimensional Stability</b>	≤ 0.2% (ISO 2551 / EN 986)					
<b>Impact Sound Insulation (ΔLw)</b>	26dB (EN ISO 10140-3)					
<b>Rating of Sound Absorption</b>	α <sub>w</sub> 0.20 (EN ISO 11654)					
<b>Sound Absorption</b>						
<b>125Hz</b>	<b>250Hz</b>	<b>500Hz</b>	<b>1000Hz</b>	<b>2000Hz</b>	<b>4000Hz</b>	(EN ISO 354)
0.01	0.02	0.10	0.26	0.34	0.47	α <sub>s</sub>
<b>Style number</b>	3383100405	4m <sup>2</sup> - 16 Tiles per Box (50 x 50 cm ± 0.20%)				




**EN 14041**





DOP: 1037/116182  
textile floor covering  
EN 1307

install with  
Tactiles®

Cert. ENP 477

Interface Europe Ltd reserve the right to change or modify specifications

[www.interface.com](http://www.interface.com)



**Mission Zero:**  
our promise to eliminate any negative impact our company may have on the environment by the year 2020.