

# SUBLIME



Paon 150 4 m  
L 47,2 - p 16,2\*



Gingembre 610 4 m  
L 86,1 - p 68,2\*



Honey 630 4 m  
L 62,9 - p 31,5\*



Champagne 730 4 m  
L 70,3 - p 41,1\*



Musc 750 4 m  
L 47,5 - p 16,4\*



Moka 760 4 m  
L 41,2 - p 12\*



Nacre 910 4 m  
L 83 - p 62,1\*



Perle 915 4 m  
L 76,1 - p 50,1\*



Céladon 920 4 m  
L 62 - p 30,4\*



Smoke 940 4 m  
L 60,3 - p 28,4\*



Ombre 970 4 m  
L 39,4 - p 10,9\*



Prusse 980 4 m  
L 34,2 - p 8,1\*

\* Indice de reflexion lumineuse / Light Reflectance Value (L:CIE Lab - p:Rhô)




Lé / Broadloom

SUBLIME

4 m

12 couleurs / colors

Action Back



<b>Structure</b>	Moquette à velours Saxony
Construction	Tufted carpet, Saxony
Struktur	Getufteter Saxony Velours
Structuur	Getuft tapijt, Saxony
Descripción	Moqueta de fibra Saxony
Struttura	Moquette velluto Saxony
Struktura	Wykładzina o runie typu welur Saksowski

**Composition** 100% Polyamide teint masse régénéré Econyl®  
**Pile material** 100% regenerated solution dyed nylon Econyl®

**Poids de velours / Pile weight**  
**Poleinsatzgewicht / Poolinzetmassa** 1430 g/m<sup>2</sup>  
**Peso fibra / Peso felpa / Gramatura**

**Poids total - NF ISO 8543 / Total weight**  
**Gesamtgewicht / Totaal gewicht** 2510 g/m<sup>2</sup>  
**Peso total / Peso totale / Masa całkowita**

**Epaisseur totale - NF ISO 1765 / Total thickness / Gesamtdicke**  
**Totale massa / Altura total** 12,9 mm  
**Spessore totale / Wysokość całkowita**

**Hauteur du velours - NF ISO 1766 / Pile height / Polhöhe / Poolhoogte** 11 mm  
**Altura fibra / Spessore felpa / Wysokość runa**

**Envers / Backing / Rückenausstattung / Rug / Soporte / Sottofondo / Podkład** Action back / Action back

<b>Jauge - Serrage (points) - Densité - NF ISO 1763</b>	
Gauge - Rows (points) - Tufts	1/10°
Teilung - Stiche (points) - Noppenzahl	48 p
Rijen - Deling (points) - Noppenaantal	189600 p/m <sup>2</sup>
Galga - Densidad (puntos)	
Scartamento - Serraggio (punti) - Densità felpa	
Zacieśnienie - Rozstaw igiel (punkty) - Gęstość	

<b>Comportement au feu</b>	Cf-s1 - collé sur ciment
Fire resistance	Cf-s1 - glued on cement
Brennverhalten	Cf-s1 - geklebt auf Zement
Brandgedrag	Cf-s1 - verlijmd op cement
Clasificación al fuego	Cf-s1 - pegado en cemento
Comportamento al fuoco	Cf-s1 - incollato su cemento
Trudnozapałność	Cf-s1 - klejone na podłożu betonowym

**LEED®: Ce produit va contribuer à gagner des points dans le cadre du Leed version 4 et répondre aux exigences relatives à la qualité des environnements intérieurs: Matériaux à faible émission.**  
**LEED®: This product can help you earn points within the framework of Leed version 4 and meet the requirements regarding indoor environmental quality: Low-emitting materials.**

**Absorption aux bruits aériens - NF EN ISO 11654**  
**Sound absorption / Schallabsorptionsgrad / Geluidsabsorptie / Absorción de los ruidos** αw 0,25  
**aéros / Isolazione acustica / Pochłanianie dźwięku**

f/Hz	125	250	500	1000	2000	4000
αs	0,03	0,08	0,18	0,44	0,61	0,84

**Pose / Entretien / Traitement**  
**Laying / Cleaning / Treatment**  
**Verlegehinweis / Reinigung / Behandlung**  
**Plaatsinstructie / Reiniging / Onderhoud** www.balsan.com  
**Instalación / Mantenimiento / Tratamiento**  
**Posa / Manutenzione / Trattamenti**  
**Układanie / Utrzymanie w czystości / Impregnacja**

BALSAN se réserve le droit de modifier les caractéristiques de ce produit tout en conservant les mêmes qualités techniques. Dans le cadre d'une utilisation professionnelle, il est fortement conseillé d'utiliser des coloris moyens et foncés pour les pièces à grand trafic. De légères variations de coloris peuvent être observées entre les différents bords de teinture. / BALSAN reserves the right to modify the characteristics of this product while keeping the same technical properties. In the context of business use, we strongly recommend the use of darker colours for heavy traffic areas. Slight differences in colour may occur between different dye baths.



# FullColors

core system

## Fil teint masse :

Très haute résistance des coloris aux UV et aux produits d'entretien les plus agressifs.

## *Solution dyed:*

*Colours are very highly resistant to UV and the most aggressive cleaning products.*

