

SPECIFICATION SHEET

ALFA

CONSTRUCTION	LOOP	
PILE FIBER COMPOSITION	100% Olefin	
YARN TYPE	BCF	
DYE METHOD	Solution Dyed	
PILE WEIGHT	550 g/m ²	
NUMBER OF TUFTS	244280/m ²	
TUFTING GAUGE	1/10"	
PRIMARY BACKING	Non-Woven	
SECONDARY BACKING	StableShield- 100% Vinyl	
OPTIONAL BACKINGS	Recova-PU Cushion, EcoShield-100% Recycled Vinyl	
TILE SIZE	50 cm x 50 cm (19.6 in x 19.6 in)	
PILE HEIGHT	3.5 mm (+/-5%)	
TOTAL HEIGHT	6.5 mm (+/-5%)	
PILE TREATMENT	Walk of Fame, Anti-Microbial (Optional)	
RECOMMENDED INSTALLATION	Ouarter Turn	



PERFORMANCE SPECIFICATION

WEAR CLASSIFICATION	HEAVY CONTRACT	
VOC EMISSION	ASTM D5116-06	<0.5 mg/m²/hour (CRI GLP)
FLAMMABILITY	ASTM D-2859//FF 1-70//16CFR 1630	Pass 8/8
CRITICAL RADIANT FLUX	ASTM E648-08	Class 1
STATIC PROPENSITY	ISO 6356	0.2 kV
COLOR FASTNESS	AATCC/16	5/5 on Grey Scale
THERMAL RESISTANCE	ISO 8302	.04m2 K/W
IMPACT SOUND INSULATION	ISO 140-8	ΔLw 23dB
SOUND ABSORPTION LEVEL	EN ISO 11654	aw: 0.15(H)
SOILING PROPENSITY	ASTM D 6540-00	4
DIMENSIONAL STABILITY	EN 986	< 0.20%
CASTOR CHAIR TEST	DIN 54324	R ≥ 2.4
SMOKE DENSITY	EN ISO 9239-1:2002	<450













































- Shading or Pile reversal is nature of cut pile carpet and it is not manufacturing defect
- Color may slightly vary from one dye lot to another dye lot
- Total weight of the product can have a normal variation of ± 5%
- We reserve to amend the above specification without prior notice due variables in raw material supplies

