

QUALITY
ORDER CODE

DATE: **17/12/2018**
REPLACES: 14/08/2014

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

CARVE CLASSIC FBP/FS
CFA

± 400
COLLECTION
1/10" CUT LOOP

PIECE DYED

PA

NON WOVEN

PES FELTBACK

± 1.180
± 2 580

± 6,0
± 10,0
± 204 880
± 39,40
± 52,00

± 15,00 / 10,00
±

± 25
PILE IN

✓

✓

✓

✓

✓

✓

✓

ANTISTATIC

✓

✓

ACBDA64D

Z-156.601-957 - PA 6 / 111 / FS

11/279
U3P3E1C0

Cl. 23 / Cl. 32

Domestic Heavy / Commercial General







LC4



Bfl-s1




QUALITY

IMPACT SOUND INSULATION	(±) dB		ISO 140/8	± 31	
SOUND ABSORPTION	(±)	α_s	ISO 354 - 125 Hz	±	
	(±)		250Hz	± 0,08	
	(±)		500Hz	± 0,35	
	(±)		1000Hz	± 0,32	
	(±)		2000Hz	± 0,43	
	(±)		4000Hz	± 0,5	
SOUND ABSORPTION	(±)	α_w	EN ISO 11654	± 0,35	
THERMAL RETENTION	(±) m ² /KW		ISO 8302	± 0,147	
TOG rating	(±)			± 1,47	
PERMANENTLY ANTISTATIC	(±) volt		ISO 6356	≤ 2000	
SURFACE RESISTANCE RoT	(±) ohm		ISO 10965	≤ 10E11	
LIGHTFASTNESS			ISO 105-B02	≥ 5	
RUBBINGFASTNESS DRY			ISO 105 X12	≥ 3-4	
RUBBINGFASTNESS WET			ISO 105 X12	≥ 3	
WATERFASTNESS CHANGE IN COLOUR			ISO 105-E01	≥ 3-4	
WATERFASTNESS STAINING			ISO 105-E01	≥ 3-4	

CARVE CLASSIC FBP/FS

LABEL CE



ALL-OVER STICK DOWN WITH EC1 APPROVED ADHESIVE - MUSHROOM TAPE ALFA-GRIP

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

FBP 400	CFA
100	RUBY
120	CORAL
251	WHEAT
261	CAMEL 1
280	HAVANNA
291	SEPIA 1
310	RUST
410	LEATHER
420	CORNSTALK
431	BAMBOO MAT 1
530	APPLE
710	ATLANTIC
790	MIDNIGHT
810	CHARCOAL
821	SLATE 1
840	MOONSHINE

FBP 400	CFA
---------	-----



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE