


# PRIMROSE SQR


## ComfyBack



Manufacturing process Tufting 1/10" Uni saxony	Méthode de fabrication Tuftée 1/10" Uni saxony	Herstellungsverfahren Getuftet 1/10" Uni saxony	Fabricatiemethode Getuft 1/10" Uni saxony
Pile composition 100% Solution dyed PA IMPREL® FINESSE	Composition du velours 100% Solution dyed PA IMPREL® FINESSE	Florzusammenstellung 100% Solution dyed PA IMPREL® FINESSE	Pool Samenstellung 100% Solution dyed PA IMPREL® FINESSE
Backing ComfyBack	Dossier ComfyBack	Rücken ComfyBack	Rug ComfyBack
Pile height Ca. 8 mm	Hauteur du velours Ca. 8 mm	Floröhe Ca. 8 mm	Poolhoogte Ca. 8 mm
Total height Ca. 12,5 mm	Hauteur totale Ca. 12,5 mm	Gesamthöhe Ca. 12,5 mm	Totale hoogte Ca. 12,5 mm
Pile weight Ca. 1.430 g/m <sup>2</sup>	Poids du velours Ca. 1.430 g/m <sup>2</sup>	Polgewicht Ca. 1.430 g/m <sup>2</sup>	Poolgewicht Ca. 1.430 g/m <sup>2</sup>
Total weight Ca. 5.300 g/m <sup>2</sup>	Poids total Ca. 5.300 g/m <sup>2</sup>	Gesamtgewicht Ca. 5.300 g/m <sup>2</sup>	Totaal gewicht Ca. 5.300 g/m <sup>2</sup>
Tuft density Ca. 232.000/m <sup>2</sup>	Nombre de points Ca. 232.000/m <sup>2</sup>	Noppenzahl Ca. 232.000/m <sup>2</sup>	Aantal noppen Ca. 232.000/m <sup>2</sup>
Size 50 x 50 cm	Dimensions 50 x 50 cm	Abmessung 50 x 50 cm	Afmetingen 50 x 50 cm
Fire class C <sub>FL</sub> -s1 (EN 13501-1)	Classement feu C <sub>FL</sub> -s1 (EN 13501-1)	Brandverhaltensklasse C <sub>FL</sub> -s1 (EN 13501-1)	Brandklasse C <sub>FL</sub> -s1 (EN 13501-1)
Fastness to light ≥ 7	Solidité à la lumière ≥ 7	Lichtechtheit ≥ 7	Lichtechtheid ≥ 7
Water fastness ≥ 4-5	Solidité à l'eau ≥ 4-5	Wasserechtheit ≥ 4-5	Waterechtheid ≥ 4-5
Thermal resistance tbc	Résistance thermique tbc	Wärmedurchlasswiderstand tbc	Warmte doorlaatweerstand tbc



**comfy  
back**



**balta**  
carpet tiles

MAINTENANCE: Spillage should be taken up promptly and surface stains removed by an appropriate method as soon as possible. In heavy traffic areas the carpet should be cleaned daily with a vacuum cleaner. Periodic maintenance should be carried out by professional cleaning staff using appropriate extraction systems. COLOUR MARCHING: As with all textile products there will be a variance in shade from batch to batch. Any samples supplied are as close a representation to the actual carpet as the production process will allow. An exact colour match between different dye batches cannot be guaranteed.

Balta Carpet Tiles • Zevensterrestraat 21 • B-9240 Zele • Tel. +32 (0)52 80 80 80 • www.baltagroup.com

# PRIMROSE SQR



Luxury Carpet Tiles



▲ 37



▲ 33



▲ 35




▲ 30



▲ 63



▲ 93



▲ 96



▲ 97



▲ 74



▲ 27

