

## York PD

|                              |                        |         |            |
|------------------------------|------------------------|---------|------------|
| <b>Manufacturing process</b> | Needlefelt             |         | ISO 2424   |
| <b>Surface aspect</b>        | Nop - Dessin           |         | ISO 2424   |
| <b>Dimensions</b>            | 100 cm, 200 cm, 400 cm |         |            |
| <b>Backing</b>               | PD                     |         | ISO 2424   |
| <b>Pile yarn composition</b> | 75% PP / 25% PES       |         |            |
| <b>Pile weight</b>           | 550 g/m <sup>2</sup>   |         |            |
| <b>Total weight</b>          | 1790 g/m <sup>2</sup>  | +/- 10% | ISO 8543   |
| <b>Pile height</b>           | 2,5 mm                 |         | ISO 1765   |
| <b>Total height</b>          | 6,2 mm                 | +/- 10% | ISO 1765   |
| <b>Flammability</b>          | Efl                    |         | EN 13501-1 |

## Floorsymbols



## Certificates



2018-01-03

Vebe Floorcoverings b.v. products are to be installed in full accordance with Vebe installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Vebe products should only be used as floorcoverings. Note: Vebe Floorcoverings b.v. reserve the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, check our internet site.

In the area of office chairs we recommend to use mats made of polycarbonate. This extends the life of your carpet.