

QUALITY
ORDER CODE

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING
SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

DATE: 19/10/2018
REPLACES: 22/08/2018

FASCINATION SB
FSC

± 400 & 500
COLLECTION
1/10" TWIST

SOLUTION DYED

ECCELENA 2-PLY

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 1.440
± 2.450

± 9,0
± 12,0
± 141.840
± 39,40
± 36,00

±
±

±

✓
✓

✓

NO SHOCK
✓

Cl. 23
Domestic Heavy



LC5



Efl



Heavy domestic / General non-domestic

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

QUALITY

DIMENSIONAL STABILITY

EN 986

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 25



SOUND ABSORPTION

(±)

α_s

ISO 354 - 125 Hz

±

(±)

250Hz

±

(±)

500Hz

±

(±)

1000Hz

±

(±)

2000Hz

±

(±)

4000Hz

±

SOUND ABSORPTION

(±)

α_w

EN ISO 11654

±

THERMAL RETENTION

(±) m²/KW

ISO 8302

± 0,137



TOG rating

(±)

± 1,37

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤

SURFACE RESISTANCE RoT

(±) ohm

ISO 10965

≤

SURFACE RESISTANCE RdT

(±) ohm

ISO 10965

≤

LIGHTFASTNESS

ISO 105-B02

≥ 5

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 3-4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 3

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01

≥ 3-4

WATERFASTNESS STAINING

ISO 105-E01

≥ 2-3

LABEL CE



LANO NV - Venetiëlaan 33
B-8530 HARELBEKE
Floor carpets to use in
buildings

RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE
FROM

AVAILABLE
FROM

COLOURS

<u>SB 400</u>	FSC	<u>SB 500</u>
0042	ANEMONE 2	0042
0212	TOBACCO 2	0212
0221	ACORN 1	0221
0250	MAGNOLIA	0250
0251	MAGNOLIA 1	0251
0260	CAMEL	0260
0272	ALMOND 2	0272
0440	IVORY	0440
0750	SKY	0750
0810	CHARCOAL	0810
0832	ASH 2	0832
0842	MOONSHINE 2	0842
0850	MOONBEAM	0850
0862	GRANITE 2	0862
0872	SILVER 2	0872
0882	PEARL 2	0882

<u>SB 400</u>	FSC	<u>SB 500</u>
---------------	------------	---------------

