

Interface® | Biosfera I Micro

SPECIFICATION

| | | | |
|----------------------------|---|---------------------------------------|---|
| Product definition | Microtuft Patterned Level Loop Tile | Style number | 60717 |
| Pile Material | 100% Recycled BCF Solution Dyed Nylon contains pre and post-consumer recycled content | Wear Classification | EN 1307 33 Heavy Contract |
| Pile Yarn Weight | 350g/m ² ± 5% | Radiant panel | (EN ISO 9239/1) Euroclass Cfl S1 (EN ISO 13501) |
| Total Weight | 4134g/m ² ± 5% | Hot Metal Nut | Pass, low radius of effects of ignition (BS 4790) |
| Pile Height | | Castor Chair Rating | ≥ 2,4 (EN 985) |
| Total Thickness | 4.8 mm ± 0,3 mm | Dimensional Stability | ≤ 0,2% (ISO 2551 / EN 986) |
| Gauge/Ends per 10cm | 5/64 - 50,4 | Vertical Electrical Resistance | 5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965) |
| Tufts per m2 | 186,480 ± 5% | Colour Fastness - Light | ≥ 7 (ISO 105/B02) |
| Backing Type | Graphlex® | Tiles per Box | 20 - 5 (50 x 50 cm ± 0,2%) |

CE
0336-CPD-8538
EN 14041:2004

Cfl-s1

BS

Quarter Turn

GUT

24975

1.3 dB

33

EN 1307

www.interface.com



Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.