



MINERAL QUARTZ

COLLECTION

L C T [®] **FIRST**
Luxury Carpet Tiles

| | | | |
|--|--|---|---|
| Manufacturing process Tufting 1/10" loop pile | Méthode de fabrication Tuftée 1/10" poil bouclé | Herstellungsverfahren Getuftet 1/10" Schlingenpol | Fabricatiemethode Getuft 1/10" lussenpool |
| Pile content 100% PP Stainsafe [®] | Composition du velours 100% PP Stainsafe [®] | Polmaterial 100% PP Fleckweg [®] | Pool Samenstelling 100% PP Stainsafe [®] |
| Pile weight Ca. 550 g/m ² | Poids du velours Ca. 550 g/m ² | Polgewicht Ca. 550 g/m ² | Poolgewicht Ca. 550 g/m ² |
| Total weight Ca. 4.300 g/m ² | Poids total Ca. 4.300 g/m ² | Gesamtgewicht Ca. 4.300 g/m ² | Totaal gewicht Ca. 4.300 g/m ² |
| Pile height Ca. 4 mm | Hauteur du velours Ca. 4 mm | Florhöhe Ca. 4 mm | Poolhoogte Ca. 4 mm |
| Total height Ca. 7 mm | Hauteur totale Ca. 7 mm | Gesamthöhe Ca. 7 mm | Totale hoogte Ca. 7 mm |
| Tuft density Ca. 212.760/m ² | Nombre de touffes Ca. 212.760/m ² | Noppenzahl Ca. 212.760/m ² | Aantal noppen Ca. 212.760/m ² |
| Size 50 x 50 cm | Dimensions 50 x 50 cm | Abmessung 50 x 50 cm | Afmetingen 50 x 50 cm |
| Packaging 5 m ² | Emballage 5 m ² | Verpackung 5 m ² | Verpakking 5 m ² |
| Antistatique < 2 kV | Antistatique < 2 kV | Antistatisch < 2 kV | Antistatisch < 2 kV |
| Fire class C _{FL} -s1 (EN 13501-1) Centexbel 0493-CPR-0130 | Classement feu C _{FL} -s1 (EN 13501-1) Centexbel 0493-CPR-0130 | Brandverhaltensklasse C _{FL} -s1 (EN 13501-1) Centexbel 0493-CPR-0130 | Brandklasse C _{FL} -s1 (EN 13501-1) Centexbel 0493-CPR-0130 |
| Sound insulation 22 dB | Isolation aux bruits d'impact 22 dB | Trittschalldämmung 22 dB | Geluidsisolatie 22 dB |
| Fastness to light 5-6 | Solidité à la lumière 5-6 | Lichtechtheit 5-6 | Lichtechtheid 5-6 |
| Water fastness 4-5 | Solidité à l'eau 4-5 | Wasserechtheit 4-5 | Waterrechtheid 4-5 |

EN 14041

16


Balta Industries - Wakkensteenweg 2
BE - 8710 Sint-Baafs-Vijve

DOP: 1010#BIOACL

Textile Floor Covering EN 1307
Notified body 0493

www.baltamedia bank.com

49D7E8F0
www.pro-dis.info



MAINTENANCE: Spillage should be taken up promptly and surface stains removed by an appropriate method as soon as possible. In heavy traffic areas the carpet should be cleaned daily with a vacuum cleaner. Periodic maintenance should be carried out by professional cleaning staff using appropriate extraction systems. COLOUR MARCHING: As with all textile products there will be a variance in shade from batch to batch. Any samples supplied are as close a representation to the actual carpet as the production process will allow. An exact colour match between different dye batches cannot be guaranteed.



MINERAL QUARTZ

C O L L E C T I O N

L C T [®] **FIRST**
Luxury Carpet Tiles




▲ 185



▲ 685



▲ 945



▲ 965