


Interface®

Elevation III

Product definition	Microtuff Patterned Level Loop Tile						
Pile Material	100% Recycled Solution Dyed Nylon						
Pile Yarn Weight	360gr/m ² ± 5%						
Total Weight	4154gr/m ² ± 5%						
Pile Height							
Total Thickness	4,8mm ± 0,5mm						
Gauge/Ends per 10cm	5/64 - 50,4						
Tufts per m2	186,480 ± 5%						
Backing Type	Graphlex®						
Wear Classification	EN 1307 33 Heavy Contract						
Radiant panel	(EN ISO 9239/1) Euroclass Cfl s1 (EN ISO 13501)						
Dimensional Stability	≤ 0,2% (ISO 2551/ EN 986)						
Impact Sound Insulation (ΔLw)	12 dB (EN ISO 10140-3)						
Rating of Sound Absorption	α _w 0,15 (EN ISO 11654)						
Sound Absorption	125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	(EN ISO 354)
	0,02	0,01	0,02	0,14	0,20	0,25	α _s
Style number	4199						5m ² - 20 Tiles per Box (50 x 50cm ± 0,20%)


EN 14041












DOP: 1037/122251
textile floor covering
EN 1307

B2E536BF
www.pro-tilt.info

install with TacTiles®



QUARTER-TURN

Interface Europe Ltd reserve the right to change or modify specifications

www.interface.com



Mission Zero:
our promise to eliminate any negative impact our company may have on the environment by the year 2020.