



Installation Method



Herringbone

Ashlar

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product WW860 **Colour** 105356 Natural Tweed **Collection** World Woven **Backing** GlasBac®

Product Specifications

Product Number	28190AK00
Product Construction	Tufted Pattern Loop
Yarn System	100% Recycled Content Type 6 Nylon
Yarn Manufacturer	Aquafil
Dye Method	100% Solution Dyed
Soil/Stain Protection	Protekt ² ®
Preservative Protection	Intersept [®]

	Imperial	Metric
Tufted Yarn Weight	17 oz/yd ²	576 g/m ²
Machine Gauge	1/10 in	39.4 ends/10cm
Pile Height	0.11 in	2.8 mm
Pile Thickness	0.065 in	1.7 mm
Stitches	10 /in	39.4 ends/10cm
Pile Density	9,415 oz/yd ³	349,106.1 g/m ³
Size	9.845 in x 39.38 in	25cm x 1m

Performance Specifications

Radiant Panel	(ASTM E-648) Passes
Smoke Density	(ASTM E 662) ≤ 450
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static	(AATCC - 134) < 3.0 KV
Dimensional Stability	AACHEN Din 54318 <.10%
Traffic Classification	Heavy
Fiber Modification Ratio	1.9 to 2.2
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition

Environmental Specifications

Total Recycled Content	76%
Recycled Content (Post Industrial)	68%
Recycled Content (Post Consumer)	8%
Indoor Air Quality	Green Label Plus #GLP0820
Ingredients and Life Cycle Impacts	Environmental Product Declaration
Other Environmental Claims	3rd Party Verified Carbon Neutral NSF/ANSI-2440 Gold - Sustainability Assessment
End Of Life	Carpet to Carpet Recycling

Technical Information

Installation	See Interface Installation Guidelines online
Maintenance	Recommended Interface Maintenance Guidelines
Reclamation	Recyclable through ReEntry [®] - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)
Warranty	15 Year Standard Carpet Warranty
Standard Backing	GlasBac [®]
Backing Options	CushionBac Renew™, GlasBac [®] , GlasBac [®] RE
Tile Size Options	25cm x 1m
Manufacturing Location	ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States